




Neutron Production Capabilities: LBNL 88-Inch Cyclotron UCB High Flux Neutron Generator

Leo Kirsch November 7, 2014



This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under contract DE-AC52-07NA27344. Lawrence Livermore National Security, LLC and the Lawrence Berkeley National Laboratory contract XXX and the University of California Office of the President

Who I am





- I'm a 2nd year grad student at UCB, post-prelim, looking to start research
- Working with Lee Bernstein in the Bay Area Nuclear Data Group funded by NA-22 and NSSC
- The NSSC is a NNSA-funded \$25 million grant to *Seven Universities Coordinating Coursework and Experience from Student to Scientist in a Partnership for Identifying and Preparing Educated Laboratory-Integrated Nuclear Experts (SUCCESS PIPELINE)*
- I've worked on the development of the HFNG and most recently on measuring $(n,n'\gamma)$

Why we care about $(n,n'\gamma)$


- Neutron transport and data for applications
 - Extended-EGAF: partial $(n,x\gamma_i)$ cross sections)
- Nuclear Structure (ENSDF)
 - Low lying states
- Statistical Models
 - Level densities, Radiative strength functions
 - Highly excited states

Deuteron Breakup n source at the 88-Inch cyclotron for $\sigma(n,n'\gamma)$





Activated Foils (29MeV D on Ta)

Meulders et al, *Phys. Med. Biol.*,
1975, 20 (2), pp 235-243





Iron spectrum

- 1 hour of data, 2uA
- natural iron: 92% Fe⁵⁶; 2% Fe⁵⁷
- Four clovers, up current to 20uA
- 64 “clean” γ /s /barn /1%N_a/cm²






HFNG – what it does





July 25th Commissioning



Monoenergetic Beam: 10⁴⁻⁶ n/s/cm²

Summary/What's Next

- Inelastic scattering capabilities at cyclotron
 - I. Deuteron Breakup: $5\text{MeV} < E_n < 60\text{MeV}$
 - II. 10^{12} n/s/cm² in situ; 10^7 n/s/cm² beam
- High Flux Neutron Generator at UCB with multiple operation modes
 - I. Ion source based DD neutron source $E_n = 2.45\text{MeV}$
 - II. 10^{8-10} n/s/cm² uniform flux in situ; 10^{4-6} n/s/cm² beam
 - III. Moderation capabilities
 - IV. Rabbit system: shuttle time $< 1\text{s}$
- What's Next at Cyclotron
 - I. Chopper to improve nTOF measurements
 - II. 4 clover detectors (Clovershare)
 - III. Neutron energy spectrum using scintillators
 - IV. Indium and Zirconium foil activation for fast fluence

Collaborators

M.S. Basunia², T. Becker⁴, L. A. Bernstein^{1,3},
J.A. Brown¹, R.B. Firestone², A M. Hurst²,
J. James, W. Kable¹, J. Labrum¹, K.N. Leung¹,
P. Renne⁴, B. Sleaford³, K. Thayer¹,
K.A. Van Bibber¹, J. Vujic¹, **C. Waltz¹**

¹ *U.C.-Berkeley Dept. of Nuclear Engineering*

² *Lawrence Berkeley National Laboratory – Nuclear Science Division*

³ *Lawrence Livermore National Laboratory*

⁴ *Berkeley Geochronology Center*